

Printing date 13.11.2017 Version number 3 Revision: 02.09.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: PENETRON® GROUT FLOOR

1.2 Relevant identified uses of the substance or mixture and uses advised against

Not applicable-Mixture of substances

Application of the substance / the mixture: Cement-based pourable flooring leveling mortar.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

PENETRON HELLAS S.A.

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: +30 210 2476803 Email: info@penetron.gr Site: www.penetron.gr

1.4 Emergency telephone number:



European Emergency Tel.: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation EC No 1272/2008 CLP:



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:





GHS05 GHS07

Signal word: Danger

Hazard-determining components of labelling:

Cement, portland, chemicals

Printing date 13.11.2017 Version number 3 Revision: 02.09.2015

Trade name: PENETRON® GROUT FLOOR

(Contd. of page 1)

Hazard statements:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture: consisting of the following components.

Ingredients according Regulation (EU) 830/2015:		
CAS: 14808-60-7 EINECS: 238-878-4	Quartz (SiO2)	40-80%
CAS: 2660-43-4 EINECS: 266-043-4	Cement, portland, chemicals Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	25-55%
CAS: 69012-64-2 EINECS: 273-761-1	Silica-Amorphous Silica fume	0.1-10%

Additional information: Quartz (SiO2): Contains less than 1% of respirable quartz (ø <50 mm)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Seek immediate medical advice.

After inhalation: Seek medical treatment in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eve contact:

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids.

Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

(Contd. on page 3)

Printing date 13.11.2017 Version number 3 Revision: 02.09.2015

Trade name: PENETRON® GROUT FLOOR

(Contd. of page 2)

After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation of vapors may cause the lower and upper respiratory irritation, cough and breathing difficulty. At higher concentrations can cause pulmonary edema.

Ingestion may cause health disorders, including stomach pain and sting, nausea and vomiting. The contact of the product with skin causes sensitization (dermatitis). Dermatitis derives from skin inflammation that begins in the skin areas that come in contact with the sensitizing agent. Skin lesions may include erythema, edema, papules, pustules, rashes, flakes, cracks and sweating phenomena vary with the phases of the disease and affected areas. In the acute phase prevail edema, erythema and sweating, chonic phases prevail flakes, dryness, cracking and thickening skin.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Avoid formation of dust.

Avoid inhalation of vapors.

Avoid contact with spilled material.

Goggles and/ or face shield, if contact with eyes or splashes are anticipated.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust, silica gel). Ensure adequate ventilation.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing.

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Handle with care. Avoid jolting, friction and impact.

(Contd. on page 4)

Printing date 13.11.2017 Version number 3 Revision: 02.09.2015

Trade name: PENETRON® GROUT FLOOR

(Contd. of page 3)

Use in well ventilated areas.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Keep only the original container or in a suitable container for this kind of product

Keep container tightly closed when not in use

Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while using the product.

Wash hands before breaks and at the end of work.

Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.

Above the threshold value (eg. TLV-TWA) of the substance or one or more substances of the product, the use of a mask is suggested with filter type B, whose class (1, 2 or 3) should be selected in relation to the limit concentration of use (ref. Regulation EN 14387). In case there are gases or vapors from different nature and / or gases with particles (aerosols, fumes, mists, etc.) should be used combined type filters. The use of protective equipment Respiratory protection is necessary if the adopted technical measures taken are not sufficient to limit worker exposure to referential threshold values. The protection provided by masks is limited. In case where the substance in question is odorless or its olfactory threshold is higher than the TLV-TWA and relevant emergency, wear a compressed air breathing apparatus (ref. Standard EN 137) or breathing external ventilation device (ref. Regulation EN 138). For a correct choice of the system of protection from the airways, see Regulation EN 529.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Printing date 13.11.2017 Version number 3 Revision: 02.09.2015

Trade name: PENETRON® GROUT FLOOR

(Contd. of page 4)

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection:



Tightly sealed goggles

Body protection:



Protective work clothing

Use working clothes with long sleeves and safety footwear for professional use of Category II (ref. Community Directive 89/686 / CEE and standard EN ISO 20344). Wash with soap and water after removing overalls.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Dust Colour: White

Grey

Odour: typical

Odour threshold: Not determined

pH value: 9-13.5

Melting point/freezing point: Not determined **Initial boiling point and boiling range:** Not determined

Flash point: Not determined

Flammability (solid, gas): Not applicable

Auto-ignition temperature: Not determined

Decomposition temperature: Not determined

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined Upper: Not determined

(Contd. on page 6)

Printing date 13.11.2017 Version number 3 Revision: 02.09.2015

Trade name: PENETRON® GROUT FLOOR

(Contd. of page 5)

Vapour pressure: Not determined

Density:Not determinedRelative density at 20 °C $1,6\pm0,5$ Kg/litVapour densityNot determinedEvaporation rateNot determined

Solubility in / Miscibility with

water: Not determined

Partition coefficient: n-octanol/water: Not determined

Viscosity:

Dynamic: Not determined **Kinematic:** Not determined

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided Stable at environment temperature.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** Avoid exposure without appropriate protective work clothing and dust masks.
- 10.5 Incompatible materials No further relevant information available.
- 10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eve damage/irritation

Potentially irritant

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

The product is classified as Specific Target Organ Toxicity after single exposure Category 3 May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

GB -

Printing date 13.11.2017 Version number 3 Revision: 02.09.2015

Trade name: PENETRON® GROUT FLOOR

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, ÎATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:Not applicable. **14.6 Special precautions for user**Not applicable.

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

UN "Model Regulation": Void

GB

Printing date 13.11.2017 Version number 3 Revision: 02.09.2015

Trade name: PENETRON® GROUT FLOOR

(Contd. of page 7)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation 1907/2006/EC

Regulation (EU) 2015/830

CLP Regulation 1272/2008/EC

The product contains less than 1% respirable quartz ($\emptyset \le 50$ microns) and therefore it is not subject to be classified as harmful to health.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

Department issuing SDS:



SUSTCHEM Engineering Ltd

REACH & Chemical Services Department

144, 3rd Septemyriou, GR 112 51, Athens, Greece

Tel.: +30 210 8252510 Fax: +30 210 8252575

E-mail: info@suschem.gr Website: www.sustchem.gr

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.